


Institute for Language, Logic and Information

TWO THEORIES OF DYNAMIC SEMANTICS

Jeroen Groenendijk
Martin Stokhof

ITLI Prepublication Series
for Logic, Semantics and Philosophy of Language LP-90-14



University of Amsterdam



Instituut voor Taal, Logica en Informatie
Institute for Language, Logic and
Information

Faculteit der Wiskunde en Informatica
(Department of Mathematics and Computer Science)
Plantage Muidergracht 24
1018TV Amsterdam

Faculteit der Wijsbegeerte
(Department of Philosophy)
Nieuwe Doelenstraat 15
1012CP Amsterdam

TWO THEORIES OF DYNAMIC SEMANTICS

Jeroen Groenendijk
Martin Stokhof
Department of Philosophy
University of Amsterdam

ITLI Prepublications
for Logic, Semantics and Philosophy of Language
ISSN 0924-2082

Received October 1990

To appear in *Jelia '90. European Workshop on Logics in AI*. Edited by Jan van Eeck. *Lecture notes in Computer Science*. Springer Verlag, Berlin.

This paper was written while we were engaged on the DYANA-project (EBRA 3715). We would like to thank Frank Veltman and Roel de Vrijer for their help.

Abstract

The dynamic view on the semantics of natural language, though stemming already from the seventies, has developed into a widely studied subject in the second half of the eighties. At present, the unification of various dynamic theories constitutes an important issue. In this paper, two theories are compared, viz. *update semantics*, and *dynamic predicate logic*. In section 1 a general characterization of the idea of a dynamic semantics for natural language is given which subsumes these two theories. Sections 2 and 3 are devoted to short expositions of each of them. In the final section 4 a comparison is made.

The ITLI Prepublication Series

1986

- 86-01 The Institute of Language, Logic and Information
 86-02 Peter van Emde Boas A Semantical Model for Integration and Modularization of Rules
 86-03 Johan van Benthem Categorical Grammar and Lambda Calculus
 86-04 Reinhard Muskens A Relational Formulation of the Theory of Types
 86-05 Kenneth A. Bowen, Dick de Jongh Some Complete Logics for Branched Time, Part I Well-founded Time,
 86-06 Johan van Benthem Logical Syntax Forward looking Operators

1987

- 87-01 Jeroen Groenendijk, Martin Stokhof Type shifting Rules and the Semantics of Interrogatives
 87-02 Renate Bartsch Frame Representations and Discourse Representations
 87-03 Jan Willem Klop, Roel de Vrijer Unique Normal Forms for Lambda Calculus with Surjective Pairing
 87-04 Johan van Benthem Polyadic quantifiers
 87-05 Víctor Sánchez Valencia Traditional Logicians and de Morgan's Example
 87-06 Eleonore Oversteegen Temporal Adverbials in the Two Track Theory of Time
 87-07 Johan van Benthem Categorical Grammar and Type Theory
 87-08 Renate Bartsch The Construction of Properties under Perspectives
 87-09 Herman Hendriks Type Change in Semantics: The Scope of Quantification and Coordination

1988

- LP-88-01 Michiel van Lambalgen *Logic, Semantics and Philosophy of Language:* Algorithmic Information Theory
 LP-88-02 Yde Venema Expressiveness and Completeness of an Interval Tense Logic
 LP-88-03 Year Report 1987
 LP-88-04 Reinhard Muskens Going partial in Montague Grammar
 LP-88-05 Johan van Benthem Logical Constants across Varying Types
 LP-88-06 Johan van Benthem Semantic Parallels in Natural Language and Computation
 LP-88-07 Renate Bartsch Tenses, Aspects, and their Scopes in Discourse
 LP-88-08 Jeroen Groenendijk, Martin Stokhof Context and Information in Dynamic Semantics
 LP-88-09 Theo M.V. Janssen A mathematical model for the CAT framework of Eurotra
 LP-88-10 Anneke Kleppe A Blissymbolics Translation Program
 ML-88-01 Jaap van Oosten *Mathematical Logic and Foundations:* Lifschitz' Realizability
 ML-88-02 M.D.G. Swaen The Arithmetical Fragment of Martin Löf's Type Theories with weak Σ -elimination
 ML-88-03 Dick de Jongh, Frank Veltman Provability Logics for Relative Interpretability
 ML-88-04 A.S. Troelstra On the Early History of Intuitionistic Logic
 ML-88-05 A.S. Troelstra Remarks on Intuitionism and the Philosophy of Mathematics
 CT-88-01 Ming Li, Paul M.B. Vitanyi *Computation and Complexity Theory:* Two Decades of Applied Kolmogorov Complexity
 CT-88-02 Michiel H.M. Smid General Lower Bounds for the Partitioning of Range Trees
 CT-88-03 Michiel H.M. Smid, Mark H. Overmars Maintaining Multiple Representations of
 Leen Torenvliet, Peter van Emde Boas Dynamic Data Structures
 CT-88-04 Dick de Jongh, Lex Hendriks Computations in Fragments of Intuitionistic Propositional Logic
 Gerard R. Renardel de Lavalette
 CT-88-05 Peter van Emde Boas Machine Models and Simulations (revised version)
 CT-88-06 Michiel H.M. Smid A Data Structure for the Union-find Problem having good Single-Operation Complexity
 CT-88-07 Johan van Benthem Time, Logic and Computation
 CT-88-08 Michiel H.M. Smid, Mark H. Overmars Multiple Representations of Dynamic Data Structures
 Leen Torenvliet, Peter van Emde Boas
 CT-88-09 Theo M.V. Janssen Towards a Universal Parsing Algorithm for Functional Grammar
 CT-88-10 Edith Spaan, Leen Torenvliet, Peter van Emde Boas Nondeterminism, Fairness and a Fundamental Analogy
 CT-88-11 Sieger van Denneheuvel, Peter van Emde Boas Towards implementing RL

X-88-01


- Marc Jumelet *Other prepublications:* On Solovay's Completeness Theorem

1989

- LP-89-01 Johan van Benthem *Logic, Semantics and Philosophy of Language:* The Fine-Structure of Categorical Semantics
 LP-89-02 Jeroen Groenendijk, Martin Stokhof Dynamic Predicate Logic, towards a compositional,
 non-representational semantics of discourse
 LP-89-03 Yde Venema Two-dimensional Modal Logics for Relation Algebras and Temporal Logic of Intervals
 LP-89-04 Johan van Benthem Language in Action
 LP-89-05 Johan van Benthem Modal Logic as a Theory of Information
 LP-89-06 Andreja Prijatelj Intensional Lambek Calculi: Theory and Application
 LP-89-07 Heinrich Wansing The Adequacy Problem for Sequential Propositional Logic
 LP-89-08 Víctor Sánchez Valencia Peirce's Propositional Logic: From Algebra to Graphs
 LP-89-09 Zhisheng Huang Dependency of Belief in Distributed Systems
 ML-89-01 Dick de Jongh, Albert Visser *Mathematical Logic and Foundations:* Explicit Fixed Points for Interpretability Logic
 ML-89-02 Roel de Vrijer Extending the Lambda Calculus with Surjective Pairing is conservative
 ML-89-03 Dick de Jongh, Franco Montagna Rosser Orderings and Free Variables
 ML-89-04 Dick de Jongh, Marc Jumelet, Franco Montagna On the Proof of Solovay's Theorem
 ML-89-05 Rineke Verbrugge Σ -completeness and Bounded Arithmetic
 ML-89-06 Michiel van Lambalgen The Axiomatization of Randomness
 ML-89-07 Dirk Roorda Elementary Inductive Definitions in HA: from Strictly Positive towards Monotone
 ML-89-08 Dirk Roorda Investigations into Classical Linear Logic
 ML-89-09 Alessandra Carbone Provable Fixed points in $\text{ID}_0 + \Omega_1$
 CT-89-01 Michiel H.M. Smid *Computation and Complexity Theory:* Dynamic Deferred Data Structures
 CT-89-02 Peter van Emde Boas Machine Models and Simulations
 CT-89-03 Ming Li, Herman Neuféglise, Leen Torenvliet, Peter van Emde Boas On Space Efficient Simulations
 CT-89-04 Harry Buhrman, Leen Torenvliet A Comparison of Reductions on Nondeterministic Space
 CT-89-05 Pieter H. Hartel, Michiel H.M. Smid A Parallel Functional Implementation of Range Queries
 Leen Torenvliet, Willem G. Vree
 CT-89-06 H.W. Lenstra, Jr. Finding Isomorphisms between Finite Fields
 CT-89-07 Ming Li, Paul M.B. Vitanyi A Theory of Learning Simple Concepts under Simple Distributions and
 Average Case Complexity for the Universal Distribution (Prel. Version)
 CT-89-08 Harry Buhrman, Steven Homer Honest Reductions, Completeness and
 Leen Torenvliet Nondeterministic Complexity Classes
 CT-89-09 Harry Buhrman, Edith Spaan, Leen Torenvliet On Adaptive Resource Bounded Computations
 CT-89-10 Sieger van Denneheuvel The Rule Language RL/1
 CT-89-11 Zhisheng Huang, Sieger van Denneheuvel Towards Functional Classification of Recursive Query Processing
 Peter van Emde Boas
 X-89-01 Marianne Kalsbeek *Other Prepublications:* An Orey Sentence for Predicative Arithmetic
 X-89-02 G. Wagemakers New Foundations: a Survey of Quine's Set Theory
 X-89-03 A.S. Troelstra Index of the Heyting Nachlass
 X-89-04 Jeroen Groenendijk, Martin Stokhof Dynamic Montague Grammar, a first sketch
 X-89-05 Maarten de Rijke The Modal Theory of Inequality
 X-89-06 Peter van Emde Boas Een Relationele Semantiek voor Conceptueel Modelleren: Het RL-project

1990

SEE INSIDE BACK COVER



Instituut voor Taal, Logica en Informatie
Institute for Language, Logic and
Information

Faculteit der Wiskunde en Informatica
(Department of Mathematics and Computer Science)
Plantage Muidergracht 24
1018TV Amsterdam

Faculteit der Wijsbegeerte
(Department of Philosophy)
Nieuwe Doelenstraat 15
1012CP Amsterdam

TWO THEORIES OF DYNAMIC SEMANTICS

Jeroen Groenendijk
Martin Stokhof
Department of Mathematics and Computer Science
University of Amsterdam

ITLI Prepublications
for Logic, Semantics and Philosophy of Language
ISSN 0924-2082

Received October 1990

To appear in *Jelia '90. European Workshop on Logics in AI*. Edited by Jan van Eyck. *Lecture notes in Computer Science*. Springer Verlag, Berlin.

This paper was written while we were engaged on the DYANA-project (EBRA 3715). We would like to thank Frank Veltman and Roel de Vrijer for their help.

1 Dynamic semantics for natural language

The standard approach to modeltheoretic semantics for natural language, to which we will refer in the sequel as *static semantics*, can be characterized as follows. The meaning of a sentence is identified with its truth-conditional content. Consequently, the interpretation of a sentence with respect to some model M is given by a recursive definition of the truth of a sentence with respect to M and certain parameters specified in M (assignments of values to variables, possible worlds, points in time, speaker, hearer, and so on.) We use the term *index* to cover whatever parameters are in use. Doing so, the meaning of a sentence in M can be identified with the set of indices with respect to which it is true in M . Other semantic notions are defined in terms of this one. For example, entailment is defined as meaning inclusion in all M . And the notion of updating an information state with a sentence is defined as taking the conjunction of the information state with the information content, i.e., the truth-conditional content, of the sentence.

By contrast, the dynamic outlook on natural language interpretation, referred to as *dynamic semantics*, starts from a fundamentally different basic notion. Not the information content, but the information change potential of a sentence is regarded as constituting its meaning. Consequently, the notion of the interpretation of a sentence with respect to a model M is given by a recursive definition of the result of updating an information state with the sentence. The meaning of a sentence with respect to M can then be identified with the update function associated with the sentence in M . This already brings out the fundamental difference between a static and a dynamic semantical system. Whereas in the former the notion of information content is the basic recursive notion, in the latter it is the notion of information change that plays this role. Finally, the dynamic notion of meaning brings along new possibilities for defining entailment. One among them is the following: ϕ entails ψ iff whenever we update an information state s with ϕ , we end up with an information state s' in which ψ is accepted or satisfied.

The key notion in the above characterization is that of information. For our present purposes, the following simple notion suffices. Information is a set of possibilities, viz., those situations which are still open. Information may concern different things, hence these possibilities may be diverse in character. For example, information may concern just the values of variables, or it may concern world-time pairs, or whatever parameters we decide to take into account. In the terminology we adopt here, information is about indices.

Information can then be represented as follows. Let I be the set of indices. An information state is a subset of I . Getting better informed is eliminating possibilities, i.e., going from an information state to a subset of that state. The minimal information state is the set of all possible indices I . A state of maximal information is a unit set $\{i\}, i \in I$. The empty set \emptyset is the absurd information state. The power set $\wp(I)$ of I , henceforth denoted by \mathcal{S} , is the

set of all information states. It is partially ordered by \subseteq , which in the present context represents the relation of ‘being at least as strong an information state as’. Updates (information state transformers) are functions from information states to information states.

We define the following notions:

Definition 1 Let s be an information state, i an index, and τ an update. Then:

1. τ is successful in s iff $\tau(s) \neq \emptyset$
2. τ is true in i iff τ is successful in $\{i\}$
3. $\downarrow\tau = \{i \mid \tau \text{ is true in } i\}$ (‘down’)
4. $\uparrow s = \lambda s': s' \cap s$ (‘up’)
5. $\tau \circ \tau' = \lambda s: \tau'(\tau(s))$ (‘sequencing’)

Bearing in mind that the dynamic meaning of a sentence is an update, 1.1 says that updating with a sentence is successful iff the resulting information state is not the absurd one. According to 1.2 the static notion of truth is still available: a sentence ϕ is true at an index i iff the state of maximal information $\{i\}$ can be successfully updated with ϕ . The \downarrow -operator defined in 1.3 retrieves the information content of a sentence from its dynamic meaning. As was remarked above, in the static set-up the notion of update is defined globally: when applied to the information content of ϕ , the \uparrow -operator defined in 1.4 returns an update which takes the intersection of an information state and the information content of ϕ . Note that for every s $\downarrow\uparrow s = s$, but not for all τ it holds that $\uparrow\downarrow\tau = \tau$. Finally, the update corresponding to a sequence of two sentences ϕ and ψ is defined in 1.5 as the composition (in reversed order) of the updates of ϕ and ψ .

Getting better informed was described above as going from an information state to a subset of it. Not every update, however, makes you better informed. Those that do we call *eliminative updates*:

Definition 2 τ is eliminative iff for every s , $\tau(s) \subseteq s$

Notice that the following holds:

- (a) $\downarrow\tau = \{i \mid \tau(\{i\}) = \{i\}\}$, if τ is eliminative

Another relevant property of updates is that of *distributivity*:

Definition 3 τ is distributive iff for every s , $\tau(s) = \bigcup_{i \in s} \tau(\{i\})$

A distributive update is one which works ‘point-wise’. For distributive updates it holds that they can be viewed also as relations between indices, instead of as functions from sets of indices to sets of indices. Generally, the relation R_τ corresponding to τ is defined by $R_\tau = \{\langle i, j \rangle \mid j \in \tau(\{i\})\}$. Then we have:

- (b) $\tau(s) = \{j \mid \exists i \in s: \langle i, j \rangle \in R_\tau\}$, if τ is distributive

Updates which are both eliminative and distributive we call *classical*:

Definition 4 τ is classical iff τ is eliminative and distributive

Classical updates have the following characteristic. By distributivity, a classical update τ is equivalent to a relation between indices. If τ is also eliminative, this relation can only consist of pairs of identical indices. And such relations can be identified with sets. Now we note the following facts (See also van Benthem 1989):

$$(c) \quad \tau(s) = s \cap \downarrow\tau, \text{ if } \tau \text{ is classical}$$

This says that if a sentence expresses a classical update, updating an information state with that sentence comes down to taking the intersection of the information state and the information content of the sentence.

Consequently, we have:

$$(d) \quad \uparrow\downarrow\tau = \tau, \text{ if } \tau \text{ is classical}$$

These observations show that a dynamic semantics which assigns only classical updates to sentences is not really dynamic after all: it is equivalent with a static semantics with a globally defined notion of update. In other words, a truly dynamic semantics will assign at least to some sentences updates which lack at least one of the properties of distributivity and eliminativity.

2 Update semantics

In this section, we sketch the basics of Veltman's system of update semantics by giving a simplified version of the simplest system for which it makes sense: propositional logic with an operator *might*. The reader is referred to Veltman 1990 for the actual system and more substantial applications.

Consider the following two examples:

- (1) It might be raining. ... It isn't raining.
- (2) It isn't raining. ... *It might be raining.

There is a marked contrast between (1) and (2), and this displays the aspect of the meaning of the modal operator *might* that is at stake here. In examples like these, *might* serves to indicate something about an information state, rather than something about the world. A sentence of the form *might* ϕ requires that ϕ be compatible with the information state. The difference between (1) and (2) is the following. In (1), it is first expressed that the information state is compatible with the possibility that it rains, while subsequently the information state is updated with the information that it does not rain. This is okay. In (2), the information state is first updated with the information that it does not rain, and once this has happened the information that it rains is no longer compatible with the information state. So (2) is out.

The aspects of update semantics which are relevant for the comparison we

are to carry out, can be captured by the following definitions. The language discussed is that of propositional logic with a sentential operator \diamond which can be ‘outsourced’ only by conjunction. A model is a pair $\langle W, V \rangle$, with W a set of possible worlds, and V a function assigning a subset of W to the atomic sentences. The set of possible worlds constitutes the set of indices of this system, so the set of information states $S = \wp(W)$. The interpretation function $[]_M$ assigns update functions to sentences. We leave out reference to M whenever this does not lead to confusion. We write $s[\phi]$ for the result of updating an information state s with ϕ , and the definition runs as follows:

Definition 5

1. $s[p] = s \cap V(p)$
2. $s[\neg\phi] = s - s[\phi]$
3. $s[\phi \wedge \psi] = s[\phi][\psi]$
4. $s[\diamond\phi] = \begin{cases} s & \text{if } s[\phi] \neq \emptyset \\ \emptyset & \text{otherwise} \end{cases}$

The update function associated with an atomic sentence is classical, as is the one assigned to a negation. As was to be expected, conjunction is interpreted as sequencing: updating s with $\phi \wedge \psi$ means updating s with ϕ first, and then updating the resulting state $s[\phi]$ with ψ . The clause for $\diamond\phi$ says that updating s with $\diamond\phi$ leaves s as it is, if updating s with ϕ would be successful, and results in the absurd information state if it would not be. This update is eliminative, but not distributive, hence it is not classical. So it is here that the dynamics of the system resides. That $[\diamond\phi]$ is not distributive follows from the fact that something may be compatible with an information state s without being compatible with all non-empty subsets of s . Since composition preserves properties of updates, all updates are eliminative, but not all are distributive.

For an explication of the contrast between (1) and (2), we need the following definition:

Definition 6 ϕ is consistent iff ϕ is successful for some s

Then we can observe that $\diamond p \wedge \neg p$ is consistent, whereas $\neg p \wedge \diamond p$ is not.

Another basic notion of update semantics is that of acceptance:

Definition 7 ϕ is accepted in s , written as $s \Vdash \phi$, iff $s \subseteq s[\phi]$

Note that since all (sequences of) sentences in this system express eliminative updates, we have that $s \Vdash \phi$ iff $s[\phi] = s$, which is the way Veltman defines acceptance.

In terms of acceptance the following notion of entailment is defined:

Definition 8 $\phi_1, \dots, \phi_n \models \psi$ iff for all M and $s: s[\phi_1]_M \dots [\phi_n]_M \Vdash \psi$

A conclusion ψ follows from a sequence of premises ϕ_1, \dots, ϕ_n if whenever an

information state s is updated with ϕ_1, \dots, ϕ_n consecutively, the result is an information state which accepts ψ . There are alternative notions of entailment available in update semantics, see Veltman 1990, van Benthem 1990.

3 Dynamic predicate logic

In this section we sketch the system of dynamic predicate logic (*DPL*). In order to facilitate comparison, we give the system in the format of update semantics. See Groenendijk & Stokhof 1989 for the original formulation and more details.

DPL is concerned mainly with a compositional analysis of anaphoric relations. The following simple examples will explain what is at stake:

- (3) A man walks in the park. He whistles
- (4) Every farmer who owns a donkey, beats it

If we were to translate these sentences in a compositional, ‘on-line’ manner, what we would end up with are the following:

- (5) $\exists x(\text{man}(x) \wedge \text{walk_in_the_park}(x)) \wedge \text{whistle}(x)$
- (6) $\forall x((\text{farmer}(x) \wedge \exists y(\text{donkey}(y) \wedge \text{own}(x, y))) \rightarrow \text{beat}(x, y))$

Of course, given the ordinary static semantics of predicate logic these formulae do not express what the sentences mean, since the final occurrence of x in (5) and of y in (6) is not bound by the corresponding existential quantifier. The idea is to provide a dynamic semantics which enables the existential quantifier to bind free occurrences of the variables it quantifies over, in such a way that (5) and (6) become equivalent with (7) and (8):

- (7) $\exists x(\text{man}(x) \wedge \text{walk_in_the_park}(x) \wedge \text{whistle}(x))$
- (8) $\forall x \forall y((\text{farmer}(x) \wedge \text{donkey}(y) \wedge \text{own}(x, y)) \rightarrow \text{beat}(x, y))$

The relevant aspects of *DPL* are the following. The language is that of ordinary first-order predicate logic. Models M are also ordinary first-order models, consisting of a domain D and an interpretation function F . The set of indices is the set G of assignments of values to variables: information is information about values of variables, information states are sets of assignments, i.e., $S = \wp(G)$, and updates are functions from sets of assignments to sets of assignments. By $g \approx_x h$ we mean that the assignments g and h differ at most with respect to the value they assign to x .

We define the update $[\approx_x]$ as follows:

Definition 9 $s[\approx_x] = \bigcup_{g \in s} \{h \mid g \approx_x h\}$

This update works as follows. If s is an information state, $s[\approx_x]$ is the information state we get from s by ‘forgetting’ all information s contains about the value of x : $s \subseteq s[\approx_x]$. So, the update function $[\approx_x]$ is non-eliminative, and it behaves rather like a ‘downdate’. Notice that since it is defined pointwise, it is

distributive.

We now define a dynamic meaning assignment to the language of first-order predicate logic using the format of update semantics:

Definition 10

1. $s[Pt_1 \dots t_n] = s \cap \{g \mid \langle [t_1]_g, \dots, [t_n]_g \rangle \in F(P)\}$
2. $s[t_1 = t_2] = s \cap \{g \mid [t_1]_g = [t_2]_g\}$
3. $s[\neg\phi] = s - \downarrow[\phi]$
4. $s[\phi \wedge \psi] = s[\phi][\psi]$
5. $s[\exists x\phi] = s[\approx_x][\phi]$

The updates associated with atomic sentences, identities, and negations constitute classical updates. Notice that the negation of ϕ is defined as the difference of the information state with the truth conditional content $\downarrow[\phi]$ of ϕ . So, when s is updated with $\neg\phi$ we get those assignments in s with respect to which ϕ is false. Conjunction is defined as sequencing: $[\phi \wedge \psi] = [\phi] \circ [\psi]$. The crucial clause is the last one. Updating an information state s with a formula $\exists x\phi$ amounts to first forgetting the information s contains about the possible values of x , and then updating the resulting state $s[\approx_x]$ with ϕ . In other words, the update $[\exists x\phi]$ is equivalent with the sequence of updates $[\approx_x] \circ [\phi]$.

Since atomic formulae, identities, and negations constitute classical updates; $[\approx_x]$ is a distributive, but non-eliminative update; and conjunction and existential quantification are defined in terms of sequencing of updates, the system as a whole is distributive and non-eliminative. So, update semantics and *DPL* are both non-classical, but in different ways.

In the original formulation of *DPL* meanings were relations between assignments, instead of, as in the present format, functions from sets of assignments to sets of assignments. In view of fact (b) mentioned in section 1, this makes no difference. Consequently, what was said in Groenendijk & Stokhof 1989 about the logic of *DPL* carries over to the present formulation. For our present purposes it suffices to discuss some basic notions and facts.

We first return to the two examples discussed above. The first example concerns sequences of sentences which, when translated compositionally turn up as formulae of the form $\exists x\phi \wedge \psi$. The interpretation of such a formula is the sequence of updates $[\exists x\phi] \circ [\psi]$, i.e., $([\approx_x] \circ [\phi]) \circ [\psi]$. Since sequencing is associative, this is the same as $[\approx_x] \circ ([\phi] \circ [\psi])$. So, from the associativity of sequencing, it immediately follows that:

$$(e) \quad \exists x\phi \wedge \psi = \exists x(\phi \wedge \psi)$$

The essential dynamic feature of *DPL* is that the binding force of an existential quantifier is not restricted to occurrences of variables inside its syntactic scope, but extends to occurrences of variables further on. This shows that a dynamic interpretation of the language of predicate logic makes it possible to translate

examples such as (3) in a compositional way.

Before we can indicate how the second kind of example, that of so-called ‘donkey-sentences’, can be dealt with, we first note that implication, disjunction and universal quantification can be defined in terms of negation, conjunction and existential quantification in the usual way:

Definition 11

1. $\phi \rightarrow \psi = \neg(\phi \wedge \neg\psi)$
2. $\phi \vee \psi = \neg(\neg\phi \wedge \neg\psi)$
3. $\forall x\phi = \neg\exists x\neg\phi$

The definition of implication makes it ‘internally dynamic’: an existential quantifier in the antecedent can bind occurrences of variables in the consequent. So we have unconditionally:

$$(f) \quad \exists x\phi \rightarrow \psi = \forall x(\phi \rightarrow \psi)$$

This feature of *DPL* makes it possible to treat donkey-sentences, such as (4), in a compositional way.

We end this section with some remarks about truth and entailment in *DPL*. The definition of the interpretation of a formula does not proceed in terms of its truth conditions. But as we saw, a global notion of truth is available: the truth conditional content of ϕ is given by $\downarrow[\phi]$. In terms of it we define the notion of satisfaction:

Definition 12 ϕ is satisfied by s , written as $s \models \phi$, iff $s \subseteq \downarrow[\phi]$

An information state s satisfies ϕ iff ϕ is true with respect to every assignment $g \in s$.

The following notion of entailment can be defined in terms of the notion of satisfaction:

Definition 13 $\phi_1, \dots, \phi_n \models \psi$ iff for all M and $s: s[\phi_1]_M \dots [\phi_n]_M \models \psi$

A conclusion ψ follows from a sequence of premisses ϕ_1, \dots, ϕ_n if whenever an information state s is updated with ϕ_1, \dots, ϕ_n consecutively, the result is an information state which satisfies ψ . Alternative notions of entailment can be defined for *DPL*, but the present notion has the nice feature of being dynamic itself. For example, we have that:

$$(g) \quad \exists xPx \models Px$$

More generally we have the following deduction theorem:

$$(h) \quad \phi_1, \dots, \phi_n \models \psi \text{ iff } \models (\phi_1 \wedge \dots \wedge \phi_n) \rightarrow \psi$$

For extensive discussion of the properties of this notion of entailment see Groenendijk & Stokhof 1989.

4 A comparison

The two theories of dynamic semantics which we presented in the previous sections are similar in their general set-up, but also differ at important points. In section 1, we showed that if all updates which a semantics assigns to sentences have both the property of distributivity and that of eliminativity, such a semantics is not essentially dynamic. Veltman's update semantics is eliminative, but lacks the property of distributivity: $\diamond\phi$ tests globally, and not pointwise, whether an information state can be successfully updated with ϕ . *DPL*, on the other hand, is distributive, but lacks eliminativity: $\exists x$ reinitializes an information state s with respect to the information it contains about the possible values of x .

The difference between the two systems also shows in that they employ different notions of entailment. In both cases an information state is updated consecutively with the premisses, but whereas in update semantics we check whether the resulting information state accepts the conclusion, in *DPL* we require that the resulting state satisfies the conclusion.

In many cases, it makes no difference which of the two notions we use. More in particular, we have the following:

- (i) $s \Vdash \phi$ iff $s \models \phi$, if $[\phi]$ is a classical update

But with respect to non-classical updates the two notions are different.

For example, in *DPL* the following holds:

- (j) $\exists x Px \Vdash \exists y Py$

If *DPL*-entailment were defined in terms of acceptance, instead of by means of satisfaction, this would not go through. All g in an information state s which is the result of an update with $\exists x Px$ satisfy $g(x) \in F(P)$. For some such g it might hold that $g(y) \notin F(P)$. But such a state cannot accept $\exists y Py$, because after updating s with it, g will no longer be in the resulting state. However, s does satisfy $\exists y Py$ precisely because we can forget all about y . The fact that for all $g \in s: g(x) \in F(P)$ guarantees that $\exists y Py$ comes out true with respect to all elements in s . It is the non-eliminative nature of existential quantification that prevents a definition in terms of acceptance.

With respect to update semantics we observe that:

- (k) $\diamond\phi \Vdash \diamond\phi$

This fact would not hold if entailment in update semantics were defined in terms of satisfaction, instead of by means of acceptance. An information state which is updated with $\diamond\phi$ may very well not satisfy $\diamond\phi$. For notice that satisfaction is defined pointwise. Consequently, if we apply the definition of truth to $\diamond\phi$ it says that $\diamond\phi$ is true with respect to w iff ϕ is true with respect w . So the following holds:

- (l) $\downarrow[\diamond\phi] = \downarrow[\phi]$

On the other hand, any s which is updated with $\diamond\phi$ accepts $\diamond\phi$, though it need not accept ϕ . Evidently, the non-distributive character of the modal operator prohibits a definition of entailment in terms of satisfaction.

What this means is that update semantics interprets modal sentences not as assertions about the world, but rather takes them as saying something about information states: $\diamond\phi$ checks whether ϕ is compatible with s , i.e., whether s can be successfully updated with ϕ . It is only consistency with information, and not truth that makes sense for modal notions interpreted along these lines. This means that modal assertions are not considered to contribute genuine information. Whenever we update an information state s with $\diamond\phi$, it will never lead to a more informative state. It either leaves s as it is, or it leads to error, i.e., to the absurd information state.

There are cases, however, where modal statements seem to have real update effects. Consider the following example (taken from Roberts (1989)):

(9) A wolf might come in. It would eat you first.

This sequence is informative in the following sense. An information state s could be such that it contains a possible world w in which a wolf comes in that doesn't eat you first. This possible world should be eliminated by updating s with this sequence of sentences. So modal assertions should have real updating effects also.

Another interesting feature of (9) is that it exhibits an anaphoric relation between expressions which are in the scope of distinct modal operators: the indefinite term *a wolf*, which is in the scope of *might*, and the pronoun *it*, which is in the scope of *would*. Evidently, in order to be able to deal with phenomena such as these, we need a dynamic semantics of both modal operators and the existential quantifier which is more than just the sum of the two, and which allows us to account for interactions between modal operators and quantifiers. So what we need is a dynamic semantics for modal predicate logic.

However, as we have seen above, the dynamic treatment of modalities in update semantics results in a non-distributive, eliminative system, whereas dynamic predicate logic is non-eliminative and distributive. Each of these two systems has an adequate notion of entailment, but for each this is a different one. If we were to combine update semantics and dynamic predicate logic in a straightforward way, the result would be a non-eliminative and non-distributive system. The question then arises what notion of entailment naturally belongs to such a system. Although the general answer to this question is not yet clear, we may observe that in such a modal predicate logic information states will concern two separate aspects, possible worlds and assignments to variables. It might very well turn out that these two aspects, though linked in certain ways, can nevertheless be treated separately to such an extent that updates can be characterized as eliminative and non-distributive with respect to the one parameter, and as distributive but non-eliminative with respect to the other. If this turns out to be the case, it might also be possible to define a notion 'in between'

acceptance and satisfaction, which can be used in defining an adequate notion of entailment.

References

- Benthem, J. v.: 1989, Semantic parallels in natural language and computation, in H. Ebbinghaus et al. (eds.), *Logic Colloquium '87*, Elsevier, Amsterdam
- Benthem, J. v.: 1990, *General Dynamics*, Prepublication LP-90-11, ITLI, University of Amsterdam, Amsterdam, To appear in *Theoretical Linguistics*
- Groenendijk, J. and Stokhof, M.: 1989, *Dynamic Predicate Logic*, Prepublication LP-89-02, ITLI, University of Amsterdam, Amsterdam, To appear in *Linguistics and Philosophy*
- Roberts, C.: 1989, Modal subordination and pronominal anaphora in discourse, *Linguistics and Philosophy* 12(4)
- Veltman, F.: 1990, Defaults in update semantics, in H. Kamp (ed.), *Conditionals, Defaults, and Belief Revision*, Edinburgh, Dyana deliverable R2.5.A

The ITLI Prepublication Series

1990

Logic, Semantics and Philosophy of Language

LP-90-01 Jaap van der Does
LP-90-02 Jeroen Groenendijk, Martin Stokhof
LP-90-03 Renate Bartsch
LP-90-04 Aarne Ranta
LP-90-05 Patrick Blackburn
LP-90-06 Gennaro Chierchia
LP-90-07 Gennaro Chierchia
LP-90-08 Herman Hendriks
LP-90-09 Paul Dekker

LP-90-10 Theo M.V. Janssen
LP-90-11 Johan van Benthem
LP-90-12 Serge Lapierre
LP-90-13 Zisheng Huang
LP-90-14 Jeroen Groenendijk, Martin Stokhof

Mathematical Logic and Foundations

ML-90-01 Harold Schellinx
ML-90-02 Jaap van Oosten
ML-90-03 Yde Venema
ML-90-04 Maarten de Rijke
ML-90-05 Domenico Zambella
ML-90-06 Jaap van Oosten

ML-90-07 Maarten de Rijke
ML-90-08 Harold Schellinx
ML-90-09 Dick de Jongh, Duccio Pianigiani
ML-90-10 Michiel van Lambalgen

Computation and Complexity Theory

CT-90-01 John Tromp, Peter van Emde Boas
CT-90-02 Sieger van Denneheuvel
Gerard R. Renardel de Lavalette
CT-90-03 Ricard Gavaldà, Leen Torenvliet
Osamu Watanabe, José L. Balcázar
CT-90-04 Harry Buhrman, Leen Torenvliet
CT-90-05 Sieger van Denneheuvel, Karen Kwast
CT-90-06 Michiel Smid, Peter van Emde Boas
CT-90-07 Kees Doets

Other Prepublications

X-90-01 A.S. Troelstra
X-90-02 Maarten de Rijke
X-90-03 L.D. Beklemishev
X-90-04
X-90-05 Valentin Shehtman
X-90-06 Valentin Goranko, Solomon Passy
X-90-07 V.Yu. Shavrukov
X-90-08 L.D. Beklemishev

X-90-09 V.Yu. Shavrukov
X-90-10 Sieger van Denneheuvel
Peter van Emde Boas
X-90-11 Alessandra Carbone
X-90-12 Maarten de Rijke
X-90-13 K.N. Ignatiev

X-90-14 L.A. Chagrova

A Generalized Quantifier Logic for Naked Infinitives
Dynamic Montague Grammar
Concept Formation and Concept Composition
Intuitionistic Categorical Grammar
Nominal Tense Logic
The Variability of Impersonal Subjects
Anaphora and Dynamic Logic
Flexible Montague Grammar
The Scope of Negation in Discourse,
towards a flexible dynamic Montague grammar
Models for Discourse Markers
General Dynamics
A Functional Partial Semantics for Intensional Logic
Logics for Belief Dependence
Two Theories of Dynamic Semantics

Isomorphisms and Non-Isomorphisms of Graph Models
A Semantical Proof of De Jongh's Theorem
Relational Games
Unary Interpretability Logic
Sequences with Simple Initial Segments
Extension of Lifschitz' Realizability to Higher Order Arithmetic,
and a Solution to a Problem of F. Richman
A Note on the Interpretability Logic of Finitely Axiomatized Theories
Some Syntactical Observations on Linear Logic
Solution of a Problem of David Guaspari
Randomness in Set Theory

Associative Storage Modification Machines
A Normal Form for PCSJ Expressions

Generalized Kolmogorov Complexity
in Relativized Separations
Bounded Reductions
Efficient Normalization of Database and Constraint Expressions
Dynamic Data Structures on Multiple Storage Media, a Tutorial
Greatest Fixed Points of Logic Programs`

Remarks on Intuitionism and the Philosophy of Mathematics,
Revised Version
Some Chapters on Interpretability Logic
On the Complexity of Arithmetical Interpretations of Modal Formulae
Annual Report 1989
Derived Sets in Euclidean Spaces and Modal Logic
Using the Universal Modality: Gains and Questions
The Lindenbaum Fixed Point Algebra is Undecidable
Provability Logics for Natural Turing Progressions of Arithmetical
Theories
On Rosser's Provability Predicate
An Overview of the Rule Language RL/1

Provable Fixed points in $\mathcal{I}\Delta_0 + \Omega_1$, revised version
Bi-Unary Interpretability Logic
Dzhaparidze's Polymodal Logic: Arithmetical Completeness,
Fixed Point Property, Craig's Property
Undecidable Problems in Correspondence Theory